

# SAFETY DATA SHEET



Diethylenetriamine, DETA

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Product name** : Diethylenetriamine, DETA

**Index number** : 612-058-00-X

**EC number** : 203-865-4

#### REACH Registration number

Registration number	Legal entity
01-2119473793-27-0001	Delamine BV

**CAS number** : 111-40-0

**Product description** : Not applicable

**Product type** : Liquid.

**Other means of identification** : DIETHYLENETRIAMINE; 2,2'-iminodi(ethylamine); diethylene triamine; 1, 2-Ethanediamine, N1-(2-aminoethyl)-; Diethylenetriamine (DETA); Diethylenetriamine-1,2-Ethanediamine, N-(2-aminoethyl)-; 1,2-Ethanediamine, N-(2-aminoethyl)-; 2,2'-Diaminodiethylamine; 1,4,7-Tri-(aza)-heptane; N-(2-Aminoethyl)-1,2-ethanediamine

**Chemical formula** : C4-H13-N3

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Product use** : Intermediate.

**Area of application** : Industrial applications.

#### Identified uses

Consumer use as an epoxy and polyurethane curing agent  
Formulation and (re)packing of substances and mixtures - Industrial  
Manufacture of substance - Industrial  
Use as a PU curing agent for rigid foam production - Industrial  
Use as a PU curing agent for rigid foam production - Professional  
Use as an epoxy curing agent - Industrial  
Use as an epoxy curing agent - Professional  
Use as an intermediate - Industrial

### 1.3 Details of the supplier of the safety data sheet

DELAMINE B.V.  
Barchman Wuytierslaan 10  
3818 LH Amersfoort  
Netherlands  
Telephone number: +31-334676897

Diethylenetriamine, DETA

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

**e-mail address of person responsible for this SDS** : SDS.Delamine@delamine.com

### 1.4 Emergency telephone number

#### Supplier

**Telephone number** : GBK/Infotrac ID 104075 : International (001) 352 323 3500 (24 hours per day)

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

**Product definition** : Mono-constituent substance

#### Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Acute Tox. 4, H302  
Acute Tox. 4, H312  
Acute Tox. 2, H330  
Skin Corr. 1B, H314  
Eye Dam. 1, H318  
Skin Sens. 1, H317  
STOT SE 3, H335

#### Classification according to Directive 67/548/EEC [DSD]

T+; R26  
Xn; R21/22  
C; R34  
Xi; R37  
R43

See Section 16 for the full text of the R phrases or H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

### 2.2 Label elements

#### **Hazard pictograms**



#### **Signal word**

: Danger

#### **Hazard statements**

: Fatal if inhaled.  
Harmful if swallowed or in contact with skin.  
Causes severe skin burns and eye damage.  
May cause an allergic skin reaction.  
May cause respiratory irritation.

#### Precautionary statements

##### **Prevention**

: Wear protective gloves: > 8 hours (breakthrough time): neoprene. Wear eye or face protection. Wear protective clothing. Do not breathe vapour. Wash thoroughly after handling.

Diethylenetriamine, DETA

## SECTION 2: Hazards identification

- Response** : **H** ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- Storage** : **H** Store in a well-ventilated place. Keep container tightly closed.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazardous ingredients** : **2,2'**-iminodiethylamine
- Supplemental label elements** : Not applicable.
- Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.
- Special packaging requirements**
- Containers to be fitted with child-resistant fastenings** : Not applicable.
- Tactile warning of danger** : Not applicable.

### 2.3 Other hazards

- Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII** : No.
- Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII** : No.
- Other hazards which do not result in classification** : Not applicable.

## SECTION 3: Composition/information on ingredients

- Substance/mixture** : Mono-constituent substance

Diethylenetriamine, DETA

### SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Classification		Type
			67/548/EEC	Regulation (EC) No. 1272/2008 [CLP]	
2,2'-iminodiethylamine	EC: 203-865-4 CAS: 111-40-0 Index: 612-058-00-X	100	T+; R26 Xn; R21/22 C; R34 Xi; R37 R43  <b>See Section 16 for the full text of the R-phrases declared above.</b>	Acute Tox. 4, H302 Acute Tox. 4, H312 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335  <b>See Section 16 for the full text of the H statements declared above.</b>	[A]

There are no additional ingredients present which, within the current knowledge of the supplier, are classified and contribute to the classification of the substance and hence require reporting in this section.

#### Type

[A] Constituent

[B] Impurity

[C] Stabilising additive

Occupational exposure limits, if available, are listed in Section 8.

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

##### Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

##### Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

##### Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

## SECTION 4: First aid measures

- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Fatal if inhaled. May cause respiratory irritation.
- Skin contact** : Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### 4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

**Suitable extinguishing media** : Use an extinguishing agent suitable for the surrounding fire. Dry sand or other suitable absorbent. Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Halones

### 5.2 Special hazards arising from the substance or mixture

**Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
nitrogen oxides

### 5.3 Advice for firefighters

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Do not breathe vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### 6.3 Methods and material for containment and cleaning up

## SECTION 6: Accidental release measures

- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.
- 6.4 Reference to other sections** : See Section 1 for emergency contact information.  
See Section 8 for information on appropriate personal protective equipment.  
See Section 13 for additional waste treatment information.

## SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapour or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### 7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 40°C (104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

### Seveso Directive - Reporting thresholds (in tonnes)

#### Danger criteria



Diethylenetriamine, DETA

## SECTION 7: Handling and storage

Category	Notification and MAPP threshold	Safety report threshold
H2: Acute toxicity 2 any route of entry or Acute toxicity 3 Inhalation route of entry	50	200
C1: Very toxic	5	20

### 7.3 Specific end use(s)

**Recommendations** : No specific data.

**Industrial sector specific solutions** : No specific data.

## SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 8.1 Control parameters

#### Occupational exposure limits

Product/ingredient name	Exposure limit values
2,2'-iminodiethylamine	<b>EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.</b> TWA: 4.3 mg/m <sup>3</sup> 8 hours. TWA: 1 ppm 8 hours.

**Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
2,2'-iminodiethylamine	DNEL	Short term Inhalation	92.1 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Short term Inhalation	2.6 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Dermal	11.4 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	15.4 mg/m <sup>3</sup>	Workers	Systemic
	DNEL	Long term Dermal	1.1 mg/cm <sup>2</sup>	Workers	Local



Diethylenetriamine, DETA

## SECTION 8: Exposure controls/personal protection

	DNEL	Long term Inhalation	0.87 mg/m <sup>3</sup>	Workers	Local
	DNEL	Short term Dermal	4.88 mg/kg bw/day	Consumers	Systemic
	DNEL	Short term Inhalation	27.5 mg/m <sup>3</sup>	Consumers	Systemic
	DNEL	Long term Dermal	4.88 mg/kg bw/day	Consumers	Systemic
	DNEL	Long term Inhalation	4.6 mg/m <sup>3</sup>	Consumers	Systemic

### PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
2,2'-iminodiethylamine	Fresh water	0.56 mg/l	Assessment Factors
	Marine	0.056 mg/l	Assessment Factors
	Fresh water sediment	1072 mg/kg dwt	-
	Marine water sediment	107.2 mg/kg dwt	-
	Soil	214 mg/kg dwt	-
	Sewage Treatment Plant	6 mg/l	Assessment Factors

## 8.2 Exposure controls

**Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Individual protection measures

**Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### Skin protection

**Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): neoprene

Diethylenetriamine, DETA

## SECTION 8: Exposure controls/personal protection

- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: neoprene Boots.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: ammonia filter (Type K) ammonia (Type K) and particulate filter
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance

- Physical state** : Liquid. [Viscous liquid.]
- Colour** : Colourless. Yellow.
- Odour** : Ammoniacal.
- Odour threshold** : Not available.
- pH** : 11.6 [Conc. (% w/w): 1%]
- Melting point/freezing point** : -39°C
- Initial boiling point and boiling range** : 207°C
- Flash point** : Closed cup: 96.7°C
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not applicable.
- Burning time** : Not applicable.
- Burning rate** : Not applicable.
- Upper/lower flammability or explosive limits** : Not available.
- Vapour pressure** : 0.021 kPa [room temperature]
- Vapour density** : 3.56 [Air = 1]
- Relative density** : Not available.
- Solubility(ies)** : Not available.
- Solubility in water** : Miscible in water.
- Partition coefficient: n-octanol/ water** : -1.58
- Auto-ignition temperature** : 358°C

Diethylenetriamine, DETA

## SECTION 9: Physical and chemical properties

- Decomposition temperature** : Not available.  
**Viscosity** : Dynamic (room temperature): 5.05 mPa·s  
**Explosive properties** : Not applicable.  
**Oxidising properties** : None.

### 9.2 Other information

- Density** : 0.959 g/cm<sup>3</sup> [20°C]  
**Physical/chemical properties comments** : No additional information.

## SECTION 10: Stability and reactivity

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : The product is stable.
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.  
 Under normal conditions of storage and use, hazardous polymerisation will not occur.
- 10.4 Conditions to avoid** : Keep away from sources of ignition - No smoking. aerosol or mist formation
- 10.5 Incompatible materials** : Reactive or incompatible with the following materials: oxidizing materials, metals and acids.  
 Chlorinated hydrocarbon.
- 10.6 Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-iminodiethylamine	LD50 Dermal	Rabbit	1045 mg/kg	-
	LD50 Oral	Rat	1620 mg/kg	-

**Conclusion/Summary** : Inhalation (Aerosol. Rat, 8 hours) : LD0= 0.07 mg/l; LD100= 0.30 mg/l

#### Irritation/Corrosion

##### Conclusion/Summary

- Skin** : Corrosive to the skin.  
**Eyes** : Highly corrosive.  
**Respiratory** : May cause respiratory irritation.

#### Sensitisation

Diethylenetriamine, DETA

## SECTION 11: Toxicological information

Product/ingredient name	Route of exposure	Species	Result
2,2'-iminodiethylamine	skin	Guinea pig	Sensitising

### Conclusion/Summary

- Skin** : May cause skin sensitisation.  
**Respiratory** : Non-sensitiser to lungs. Not classified for respiratory sensitisation.

### Mutagenicity

- Conclusion/Summary** : Not mutagenic in a standard battery of genetic toxicological tests.

### Carcinogenicity

- Conclusion/Summary** : Dermal No carcinogenic effect. Not classified as dangerous NOAEL = 56.3mg/kg bw/day  
 Oral No data available for this end-point, hence this classification is not considered to be applicable.  
 Inhalation No data available for this end-point, hence this classification is not considered to be applicable.

### Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Developmental toxin	Species	Dose	Exposure
2,2'-iminodiethylamine	-	Equivocal	Equivocal	Rat	Oral	90 days

- Conclusion/Summary** : Fertility NOAEL = 30mg/kg bw/day  
 Developmental Toxicity: NOAEL = 30mg/kg bw/day  
 Data inconclusive.  
 Not fully tested.  
 Not classified.  
 Further studies (REACH Annex IX/ X) have been proposed

### Teratogenicity

- Conclusion/Summary** : No known significant effects or critical hazards.

### Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
2,2'-iminodiethylamine	Category 3	Not applicable.	Respiratory tract irritation

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

- Information on the likely routes of exposure** : Routes of entry anticipated: Oral, Dermal.  
 Routes of entry not anticipated: Inhalation.

### Potential acute health effects

- Eye contact** : Causes serious eye damage.

Diethylenetriamine, DETA

## SECTION 11: Toxicological information

- Inhalation** : Fatal if inhaled. May cause respiratory irritation.
- Skin contact** : Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.
- Ingestion** : Harmful if swallowed. Corrosive to the digestive tract. Causes burns.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing
- Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur
- Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

- Potential immediate effects** : No specific data.
- Potential delayed effects** : No specific data.

#### Long term exposure

- Potential immediate effects** : No specific data.
- Potential delayed effects** : No specific data.

#### Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-iminodiethylamine	Chronic NOAEL Oral Chronic NOAEL Dermal Sub-chronic NOAEL Inhalation Vapour	Rat Rat Rat	70 mg/kg 114 mg/kg 550 mg/m <sup>3</sup>	- - 6 hours

- Conclusion/Summary** : Cannot be classified.
- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Diethylenetriamine, DETA

## SECTION 11: Toxicological information

**Absorption** : Rapidly absorbed.  
**Metabolism** : Slowly metabolised.  
**Elimination** : Excreted via the faeces. Excreted via the urine.

**Other information** : No specific data.

## SECTION 12: Ecological information

### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2,2'-iminodiethylamine	EC50 32.7 mg/l	Micro-organism	3 hours
	NOEC 6 mg/l	Micro-organism	3 hours
	Acute EC50 1164 mg/l Fresh water	Algae	72 hours
	Acute EC50 32 mg/l Fresh water	Daphnia	48 hours
	Acute LC50 430 mg/l Fresh water	Fish	96 hours
	Acute NOEC 10 mg/l Fresh water	Algae	72 hours
	Chronic NOEC 5.6 mg/l Fresh water	Daphnia	21 days
	Chronic NOEC 10 mg/l Fresh water	Fish	28 days

**Conclusion/Summary** : PNEC Intermittent release.= 0.32 mg/l

### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,2'-iminodiethylamine	-	87 % - Readily - 21 days	-	-

**Conclusion/Summary** : Readily biodegradable. Toxic, not persistent. This substance is not expected to bioaccumulate through food chains in the environment.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2'-iminodiethylamine	Fresh water 28 days, 20°C	-	Readily

### 12.3 Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
2,2'-iminodiethylamine	-1.58	0.3 to 6.3	low

### 12.4 Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : 19.111

**Mobility** : No specific data.

### 12.5 Results of PBT and vPvB assessment

**PBT** : No.

**vPvB** : No.

Diethylenetriamine, DETA

## SECTION 12: Ecological information

**12.6 Other adverse effects** : No known significant effects or critical hazards.

## SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

### 13.1 Waste treatment methods

#### Product

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.





**Hazardous waste** : The classification of the product may meet the criteria for a hazardous waste.

#### Packaging

**Methods of disposal** : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

**Special precautions** : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
<b>14.1 UN number</b>	UN2079	UN2079	UN2079	UN2079
<b>14.2 UN proper shipping name</b>	DIETHYLENETRIAMINE	DIETHYLENETRIAMINE	DIETHYLENETRIAMINE	Diethylenetriamine
<b>14.3 Transport hazard class(es)</b>	8 	8 	8 	8 
<b>14.4 Packing group</b>	II	II	II	II
<b>14.5 Environmental hazards</b>	No.	Yes.	No.	No.



Diethylenetriamine, DETA

## SECTION 14: Transport information

<p><b>Additional information</b></p>	<p><b>Hazard identification number</b> 80</p> <p><b>Limited quantity</b> 1 L</p> <p><b>Tunnel code</b> (E)</p>	<p>The product is only regulated as an environmentally hazardous substance when transported in tank vessels.</p>	<p><b>Emergency schedules (EmS)</b> F-A, S-B</p>	<p><b>Passenger and Cargo Aircraft</b> Quantity limitation: 1 L Packaging instructions: 851</p> <p><b>Cargo Aircraft Only</b> Quantity limitation: 30 L Packaging instructions: 855</p> <p><b>Limited Quantities - Passenger Aircraft</b> Quantity limitation: 0.5 L Packaging instructions: Y840</p>
--------------------------------------	--	--	--	---

**14.6 Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** : Not available.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU Regulation (EC) No. 1907/2006 (REACH)

##### Annex XIV - List of substances subject to authorisation

##### Substances of very high concern

None of the components are listed.

**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.

#### Other EU regulations

**Europe inventory** : All components are listed or exempted.

#### Seveso Directive

This product is controlled under the Seveso Directive.

#### Danger criteria

Diethylenetriamine, DETA

## SECTION 15: Regulatory information

### Category

H2: Acute toxicity 2 any route of entry or Acute toxicity 3 Inhalation route of entry  
C1: Very toxic

**15.2 Chemical Safety Assessment** : Complete.

**15.3 Registration status** : Applicable.

## SECTION 16: Other information

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms** : ATE = Acute Toxicity Estimate  
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
EUH statement = CLP-specific Hazard statement  
PBT = Persistent, Bioaccumulative and Toxic  
PNEC = Predicted No Effect Concentration  
RRN = REACH Registration Number  
vPvB = Very Persistent and Very Bioaccumulative

**Key literature references and sources for data** : Regulation (EC) No. 1272/2008 [CLP]; European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR), concluded in Geneva on 30 September 1957 plus amendments (Uniform text: Journal of Laws 27/2009 pos. 162 plus amendments); Regulation for the transport of dangerous materials on the Rhine (ADN); Occupational exposure limits; International regulations

### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Acute Tox. 4, H302	Expert judgment
Acute Tox. 4, H312	Expert judgment
Acute Tox. 2, H330	Expert judgment
Skin Corr. 1B, H314	Expert judgment
Eye Dam. 1, H318	Expert judgment
Skin Sens. 1, H317	Expert judgment
STOT SE 3, H335	Expert judgment

**Full text of abbreviated H statements** : H302 Harmful if swallowed.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H330 Fatal if inhaled.  
H335 May cause respiratory irritation.

Diethylenetriamine, DETA

## SECTION 16: Other information

<b>Full text of classifications [CLP/GHS]</b>	: Acute Tox. 2, H330 Acute Tox. 4, H302 Acute Tox. 4, H312 Eye Dam. 1, H318 Skin Corr. 1B, H314 Skin Sens. 1, H317 STOT SE 3, H335	ACUTE TOXICITY (inhalation) - Category 2 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN CORROSION/IRRITATION - Category 1B SKIN SENSITIZATION - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract irritation) - Category 3
<b>Full text of abbreviated R phrases</b>	: R26- Very toxic by inhalation. R21/22- Harmful in contact with skin and if swallowed. R34- Causes burns. R37- Irritating to respiratory system. R43- May cause sensitisation by skin contact.	
<b>Full text of classifications [DSD/DPD]</b>	: T+ - Very toxic C - Corrosive Xn - Harmful Xi - Irritant	
<b>Training advice</b>	: Ensure operatives are trained to minimise exposures. Training staff on good practice.	
<b>Date of issue/ Date of revision</b>	: 18/06/2015	
<b>Date of previous issue</b>	: 15/04/2014	
<b>Version</b>	: 10	

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Consumer

Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

Section 1 Title

**Short title of the exposure scenario/List of use descriptors** **Identified use name:** Consumer use as an epoxy and polyurethane curing agent  
**Sector of end use:** SU21  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f  
**Market sector by type of chemical product:** PC01  
**Specific Environmental Release Category:** FEICA 11

**Processes and activities covered by the exposure scenario** Covers the use in consumer application of do-it-yourself glue  
**Assessment Method** See Section 3

Section 2 Operational conditions and risk management measures

Section 2.1 Control of environmental exposure

Contributing scenario controlling environmental exposure for 0:

Consumer use  
**Product characteristics:** Physical form of product : Liquid.  
**Concentration of substance in mixture or article:** Covers concentrations up to 35%  
**Amounts used:** 10700 Tonnes/year  
**Fraction of EU tonnage used in region** 0.1  
**Regional use tonnage** Not available.  
**Fraction of Regional tonnage used locally** Not available.  
**Annual site tonnage** Not available.  
**Average Local Daily Tonnage (kg/day)** Not available.  
**Maximum daily site tonnage** Not available.  
**Frequency and duration of use:** Continuous release  
**Emission Days (days/year)** 365  
**Environment factors not influenced by risk management:**  
**Local freshwater dilution factor** 10 Default  
**Local marine water dilution factor** 100 Default  
**Other given operational conditions affecting environmental exposure:**  
**Release fraction to air from process (initial release prior to RMM)** 0  
**Release fraction to soil from process (initial release prior to RMM)** 0  
**Release fraction to wastewater from process (initial release prior to RMM)** 9.00E-03  
**Conditions and measures related to municipal sewage treatment plant:**  
**Estimated substance removal from wastewater via on-site sewage treatment** 92.6%  
**Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs** Not available.

**Diethylenetriamine, DETA**

**Identified use name:** Consumer use as an epoxy and polyurethane curing agent  
**Sector of end use:** SU21  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f  
**Market sector by type of chemical product:** PC01

Maximum allowable site tonnage (M <sub>safe</sub> ) based on release following total wastewater treatment removal	Not available.
Assumed on-site sewage treatment plant flow	Not available.
Local release to soil:	0
Local release to air:	0
Local release to sewage:	5.30E-02
Fraction of substance in end-use products:	Not applicable
Fraction of main source to local environment:	0.002

## Section 2.2 Control of consumer exposure

### Contributing scenario controlling consumer exposure for 0: Glues DIY-use (carpet glue, tile glue, wood parquet glue)

Consumer use	
Product characteristics:	Physical form of product : Liquid.
Concentration of substance in mixture or article	Covers concentrations up to 35%
Physical state:	Liquid. Vapour pressure 20.3 Pa*s
Human factors not influenced by risk management:	None identified.
Conditions and measures related to information and behavioural advice to consumers	Covers use under typical household ventilation.
Contributing scenarios: Operational conditions and risk management measures	

## Section 3 Exposure estimation and reference to its source

### Section 3.1 Environment - Exposure estimation

#### Contributing scenario controlling environmental exposure for 0:

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Regional PEC : 1.71E-03	Not applicable.
air (direct + STP)	Not applicable.	Regional PEC: 2.06E-05	Not applicable.
Soil (direct releases only)	Not applicable.	Regional PEC natural soil[Total ]: 1.54E-03 Regional PEC industrial soil [ Total ]: 1.54E-03	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PEC <sub>stp</sub> ) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.00185; Surface water, Dissolved Annual average : 0.00185;	Not applicable.
Marine water mg/l	Not applicable.	Local/During emission/Dissolved: 0.00018;Annual average,Local/Dissolved, 0.00018; Regional PEC[Total]: 1.66E-04	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	During emission :3.55; Regional PEC : 5.66E+00	Not applicable.
Marine water sediment mg/kg dwt	Not applicable.	During emission: 0.350; Regional PEC: 4.68E-01	Not applicable.
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>

**Diethylenetriamine, DETA**

**Identified use name:** Consumer use as an epoxy and polyurethane curing agent

**Sector of end use:** SU21

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC08c, ERC08f

**Market sector by type of chemical product:** PC01

<b>Agricultural soil averaged mg/kg dwt</b>	Not applicable.	0.0434, 30 days; 0.0153, 180 days;Regional PEC: 4.43E-03	Not applicable.
<b>Grassland averaged mg/kg dwt</b>	Not applicable.	0.007, 180 days	Not applicable.
<b>Groundwater mg/l</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
<b>During emission mg/m<sup>3</sup></b>	Not applicable.	Not applicable.	Not applicable.
<b>Annual average mg/m<sup>3</sup></b>	Not applicable.	2.06-05	Not applicable.
<b>Annual deposition mg/m<sup>2</sup>/d</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Micro-organism mg/l</b>	Not applicable.	0	Not applicable.

### Section 3.2 Exposure estimation - Consumers

#### Exposure estimation and reference to its source - Consumers: 2: Glues DIY-use (carpet glue, tile glue, wood parquet glue)

	<b>Contributing scenario:</b>	<b>Frequency (1/Year):</b>	<b>Weight fraction of substance in the article::</b>	<b>Body weight:</b>	<b>Calculation method:</b>
<b>Exposure estimation and reference to its source - Consumers: 0: Glues DIY-use (carpet glue, tile glue, wood parquet glue)</b> <b>Inhalation :</b> <b>Mode of release:</b>	Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.

**Exposure estimation and reference to its source - Consumers: 0: Glues DIY-use (carpet glue, tile glue, wood parquet glue)**  
**Inhalation :**  
**Mode of release:**

Not applicable.

#### Exposure estimation and reference to its source - Consumers: 1: Glues DIY-use (carpet glue, tile glue, wood parquet glue)

<b>Exposure (minutes):</b>	<b>Application duration:</b>	<b>Amount/concentration applied (g):</b>	<b>Room volume (m<sup>3</sup>):</b>	<b>Room volume x ventilation rate: (l/h):</b>
Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.

<b>Release area (cm2):</b>	<b>Temperature (°C):</b>	<b>Mass transfer rate:</b>	<b>Contributing scenario Molecular weight (g/mole):</b>	<b>Uptake fraction (Update model):</b>	<b>Inhalation rate:</b>
Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.	Not applicable.

#### Dermal:

**Application methods:** Not applicable.

<b>Surface area (Skin contact area) cm2:</b>	<b>Product amount (g):</b>	<b>Uptake fraction (Update model):</b>	<b>Inhalation event (mg/m<sup>3</sup>):</b>
Not applicable.	Not applicable.	Not applicable.	Dermal : Not applicable , Inhalation :0.227 mg/m <sup>3</sup>

<b>Inhalation mg/m<sup>3</sup> (Concentration on day of exposure):</b>	<b>Dermal load (mg/cm2):</b>	<b>Dermal External dose (mg/kg bw):</b>	<b>Dermal (Internal dose) mg/kg bw/day:</b>
Not applicable.	Not applicable.	Not applicable.	0.538

<b>Dermal (External dose) mg/kg bw/day:</b>	<b>Inhalation event/Exposure mg/m<sup>3</sup> (Short term exposure):</b>	<b>Dermal systemic exposure (external dose) with gloves (90% efficiency) mg/kg bw/day (Long term exposure):</b>	<b>Inhalation (mg/kg/day) Long term exposure:</b>
Acute :0.538 mg/kg bw/day	0.227	0.0044 mg/kg bw/day	1.4E-5 mg/kg/day

**Diethylenetriamine, DETA**

**Identified use name:** Consumer use as an epoxy and polyurethane curing agent

**Sector of end use:** SU21

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC08c, ERC08f

**Market sector by type of chemical product:** PC01

**Section 3.3 Exposure estimation- Consumers****Contributing scenario controlling consumer exposure for 3: Glues DIY-use (carpet glue, tile glue, wood parquet glue)**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
Long term exposure, Systemic, Dermal	Not applicable.	0.0044	Not applicable.
Long term exposure, Systemic, Inhalable	Not applicable.	1.4E-5	Not applicable.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Systemic, Oral	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Not applicable.	0.538	Not applicable.
Short term exposure, Systemic, Inhalable		0.227	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Oral	Not applicable.	Not applicable.	Not applicable.

**Section 4: Guidance to DU to evaluate whether he works inside the boundaries set by the ES**

<b>Environment</b>	Not available.
<b>Health</b>	Not available.

**Section 5. Remarks: Additional good practice advice beyond the REACH CSA**

<b>Environment</b>	Not applicable.
<b>Health</b>	Not applicable.
<b>Additional guidance</b>	Not applicable.

**Diethylenetriamine, DETA****Identified use name:** Consumer use as an epoxy and polyurethane curing agent**Sector of end use:** SU21**Subsequent service life relevant for that use:** No.**Environmental Release Category:** ERC08c, ERC08f**Market sector by type of chemical product:** PC01

22/110



Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

Section 1: Title

**Short title of the exposure scenario/List of use descriptors** **Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02  
**Specific Environmental Release Category:** FEICA 2

**Processes and activities covered by the exposure scenario** Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities. also includes combined formulation/reaction to DETA-adducts

Section 2: Operational conditions and risk management measures

Section 2.1 Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Formulation of preparations

**Amounts used:** 43000 Tonnes/year  
**Fraction of EU tonnage used in region** 1  
**Regional use tonnage** Not available.  
**Fraction of Regional tonnage used locally** Not available.  
**Annual site tonnage** Not available.  
**Average Local Daily Tonnage (kg/day):** Not available.  
**Maximum daily site tonnage** 30000  
**Frequency and duration of use:** Continuous release  
**Emission Days (days/year)** 220

Environment factors not influenced by risk management:

**Local freshwater dilution factor** 10  
**Local marine water dilution factor** 100

Other given operational conditions affecting environmental exposure:

**Release fraction to air from process (initial release prior to RMM)** 6.00E-03  
**Release fraction to soil from process (initial release prior to RMM)** 0.00E+00  
**Release fraction to wastewater from process (initial release prior to RMM)** 0.00E+00  
**Release fraction to air from wide dispersive use (regional only)** Not available.  
**Release fraction to soil from wide dispersive use (regional only)** Not available.

Diethylenetriamine, DETA

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02

Release fraction to wastewater from wide dispersive use	Not available.
<b>Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:</b>	
Treat air emission to provide a typical removal efficiency of	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of	Not available.
<b>Conditions and measures related to municipal sewage treatment plant:</b>	
Estimated substance removal from wastewater via on-site sewage treatment	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs	92.6%
Maximum allowable site tonnage (M <sub>Safe</sub> ) based on release following total wastewater treatment removal	7987900 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	1.80E+02
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.15

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

<b>Product characteristics:</b>	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently)
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented Assumes activities are at ambient temperature (unless stated differently).
<b>Contributing scenarios: Operational conditions and risk management measures</b>	
Continuous process Mixing operations (closed systems) No sampling:	No other specific measures identified.
Bulk product storage closed systems:	No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

<b>Product characteristics:</b>	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently)
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented Assumes activities are at ambient temperature (unless stated differently).
<b>Contributing scenarios: Operational conditions and risk management measures</b>	

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC02

Continuous process Mixing operations (closed systems) With sample collection: No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Use in contained batch processes Mixing operations (closed systems) With sample collection: No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Batch process Mixing operations (open systems) With sample collection: Provide extract ventilation to points where emissions occur.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)**

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Mixing operations (open systems): Provide extract ventilation to points where emissions occur. Wear suitable gloves tested to EN374.

**Respiratory protection:**

None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with type A filter or better.

**Respiratory protection:**

None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 100%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented

Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC02

Bulk transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

**Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Drum and small package filling Dedicated facility: Ensure operation is undertaken outdoors. Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Drum and small package filling Dedicated facility With local exhaust ventilation: Ensure material transfers are under containment or extract ventilation.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

**Contributing scenario controlling worker exposure for 8: Use a laboratory reagent**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02

### Section 3: Exposure estimation

#### Section 3.1 Environment - Exposure estimation

##### Contributing scenario controlling environmental exposure for 0: Formulation of preparations

	<b>Release from point source (local exposure estimation) kg/ day</b>	<b>Total release for regional exposure estimation kg/day</b>	<b>Justification</b>
<b>Waste water</b>	Not applicable.	Not applicable.	Not applicable.
<b>Surface water</b>	Not applicable.	Not applicable.	Not applicable.
<b>air (direct + STP)</b>	Not applicable.	Not applicable.	Not applicable.
<b>Soil (direct releases only)</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
<b>Concentration in sewage (PECstp) mg/l</b>	Not applicable.	Not applicable.	
<b>Concentration in sewage sludge mg/kg dwt</b>	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Fresh water mg/l</b>	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
<b>Marine water mg/l</b>	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
<b>Intermittent release. mg/l</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
<b>Fresh water sediment mg/kg dwt</b>	Not applicable.	3.2	During emission
<b>Marine water sediment mg/kg dwt</b>	Not applicable.	0.314	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
<b>Agricultural soil averaged mg/kg dwt</b>	Not applicable.	0.804, 30 days; 0.269, 180 days	Not applicable.
<b>Grassland averaged mg/kg dwt</b>	Not applicable.	0.119, 180 days	Not applicable.
<b>Groundwater mg/l</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
<b>During emission mg/m<sup>3</sup></b>	Not applicable.	Not applicable.	Not applicable.
<b>Annual average mg/m<sup>3</sup></b>	Not applicable.	0.0301	Not applicable.
<b>Annual deposition mg/m<sup>2</sup>/d</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Micro-organism mg/l</b>	Not applicable.	0	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Continuous process Mixing operations (closed systems) No sampling; Bulk product storage closed systems	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Continuous process Mixing operations (closed systems) No sampling; Bulk product storage closed systems	0.04	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Continuous process Mixing operations (closed systems) No sampling; Bulk product storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Continuous process Mixing operations (closed systems) No sampling; Bulk product storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Continuous process Mixing operations (closed systems) No sampling; Bulk product storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Continuous process Mixing operations (closed systems) With sample collection	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Continuous process Mixing operations (closed systems) With sample collection	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Continuous process Mixing operations (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Continuous process Mixing operations (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Continuous process Mixing operations (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC02



**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Use in contained batch processes Mixing operations (closed systems) With sample collection	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Use in contained batch processes Mixing operations (closed systems) With sample collection	12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Use in contained batch processes Mixing operations (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Use in contained batch processes Mixing operations (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Use in contained batch processes Mixing operations (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Batch process Mixing operations (open systems) With sample collection; Aerosols	6.86; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Batch process Mixing operations (open systems) With sample collection; Aerosols	2.15; 0.50	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Batch process Mixing operations (open systems) With sample collection; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Batch process Mixing operations (open systems) With sample collection; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Batch process Mixing operations (open systems) With sample collection; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC02

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Mixing operations (open systems); Aerosols	2.74; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Mixing operations (open systems); Aerosols	2.15; 0.50	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Equipment cleaning and maintenance	6.02; 4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC02

**Section 3.2 Workers - Exposure estimation**

**Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Bulk transfers Dedicated facility; Material transfers Dedicated facility	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Bulk transfers Dedicated facility; Material transfers Dedicated facility	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation**

**Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility With local exhaust ventilation	1.37; 6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility With local exhaust ventilation	9.03; 2.15	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility With local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility With local exhaust ventilation	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC02

<b>Short term exposure, Local, Dermal</b>	Drum and small package filling Dedicated facility; Drum and small package filling Dedicated facility With local exhaust ventilation	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation**

**Contributing scenario controlling worker exposure for 8: Use a laboratory reagent**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Laboratory activities	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 4: Guidance to check compliance with the exposure scenario**

<b>Environment</b>	Not available.
<b>Health</b>	Not available.

**Section 5. Remarks: Additional good practice advice beyond the REACH CSA**

<b>Environment</b>	Not applicable.
<b>Health</b>	Not applicable.
<b>Additional Good Practices</b>	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Formulation and (re)packing of substances and mixtures - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC02

**33/110**

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

Section 1: Title

**Short title of the exposure scenario/List of use descriptors** **Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

**Processes and activities covered by the exposure scenario** Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities.

Section 2: Operational conditions and risk management measures

Section 2.1 Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Manufacture of substances

Amounts used:

Fraction of EU tonnage used in region	Not available.
Regional use tonnage	Not available.
Fraction of Regional tonnage used locally	Not available.
Annual site tonnage	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage	Not available.

**Frequency and duration of use:** Continuous release  
**Emission Days (days/year)** 300

**Environment factors not influenced by risk management:**  
**Local freshwater dilution factor** 4462  
**Local marine water dilution factor** Not available.

**Other given operational conditions affecting environmental exposure:**  
**Release fraction to air from process (initial release prior to RMM)** Not available.  
**Release fraction to soil from process (initial release prior to RMM)** Not available.  
**Release fraction to wastewater from process (initial release prior to RMM)** Not available.  
**Release fraction to air from wide dispersive use (regional only)** Not available.  
**Release fraction to soil from wide dispersive use (regional only)** Not available.  
**Release fraction to wastewater from wide dispersive use** Not available.

Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:

Diethylenetriamine, DETA

**Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

Treat air emission to provide a typical removal efficiency of	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of	Not available.
Conditions and measures related to municipal sewage treatment plant:	Sewage sludge incineration
Estimated substance removal from wastewater via on-site sewage treatment	60%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs	60%
Conditions and measures related to external treatment of waste for disposal:	Store finished products in closed containers (e.g., bulk tanks, drums, cans). Incinerate, absorb, or adsorb vapours stripped from solution whenever necessary.
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Fraction of substance in end-use products:	1
Fraction of main source to local environment:	1

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently)
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	
General exposures Continuous process closed systems:	No other specific measures identified.

Bulk product storage closed systems: No other specific measures identified.

Respiratory protection: None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently)
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	
General exposures Continuous process With sample collection closed systems:	No other specific measures identified.

Respiratory protection: None.

**Diethylenetriamine, DETA**

**Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
General exposures Use in contained batch processes With sample collection: No other specific measures identified.

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
General exposures Batch process With sample collection open systems: Provide extract ventilation to points where emissions occur.

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**

**Diethylenetriamine, DETA**

**Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01



Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with type A filter or better.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Bulk transfers Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 6: Use a laboratory reagent

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

## Section 3: Exposure estimation

### Section 3.1 Environment - Exposure estimation

#### Contributing scenario controlling environmental exposure for 0: Manufacture of substances

	<b>Release from point source (local exposure estimation) kg/day</b>	<b>Total release for regional exposure estimation kg/day</b>	<b>Justification</b>
<b>Waste water</b>	Not applicable.	Not applicable.	Not applicable.
<b>Surface water</b>	Not applicable.	Not applicable.	Not applicable.
<b>air (direct + STP)</b>	Not applicable.	Not applicable.	Not applicable.
<b>Soil (direct releases only)</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
<b>Concentration in sewage (PECstp) mg/l</b>	Not applicable.	Not applicable.	
<b>Concentration in sewage sludge mg/kg dwt</b>	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Fresh water mg/l</b>	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.537; Surface water, Dissolved Annual average : 0.442	Not applicable.
<b>Marine water mg/l</b>	Not applicable.	During emission Resulting PEC local, water (mg/l): Not applicable; Annual average, Dissolved, Resulting PEC local, water (mg/l): Not applicable	Not applicable.
<b>Intermittent release. mg/l</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
<b>Fresh water sediment mg/kg dwt</b>	Not applicable.	1028.3	During emission
<b>Marine water sediment mg/kg dwt</b>	Not applicable.	Not applicable	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
<b>Agricultural soil averaged mg/kg dwt</b>	Not applicable.	0.002; 30, 180 days	Not applicable.
<b>Grassland averaged mg/kg dwt</b>	Not applicable.	0.002, 180 days	Not applicable.
<b>Groundwater mg/l</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
<b>During emission mg/m<sup>3</sup></b>	Not applicable.	Not applicable.	Not applicable.
<b>Annual average mg/m<sup>3</sup></b>	Not applicable.	2.65E-05	Not applicable.
<b>Annual deposition mg/m<sup>2</sup>/d</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Micro-organism mg/l</b>	Not applicable.	0.019	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	General exposures Continuous process closed systems; Bulk product storage closed systems	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures Continuous process closed systems; Bulk product storage closed systems	0.04	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Continuous process With sample collection closed systems	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Continuous process With sample collection closed systems	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures Continuous process With sample collection closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures Continuous process With sample collection closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures Continuous process With sample collection closed systems	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures Use in contained batch processes With sample collection	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures Use in contained batch processes With sample collection	12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal		Not applicable	

**Diethylenetriamine, DETA**

**Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

	General exposures Use in contained batch processes With sample collection		Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures Use in contained batch processes With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures Use in contained batch processes With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	General exposures Batch process With sample collection open systems	6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures Batch process With sample collection open systems	2.15	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures Batch process With sample collection open systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures Batch process With sample collection open systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures Batch process With sample collection open systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Equipment cleaning and maintenance	6.02; 4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Equipment cleaning and maintenance	Not applicable	Not applicable.
	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

**Short term exposure, Systemic, Combined**

<b>Short term exposure, Local, Dermal</b>	Equipment cleaning and maintenance	Not applicable	Not applicable.
---	------------------------------------	----------------	-----------------

<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
--	-----------------	-----------------	-----------------

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Bulk transfers Material transfers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Bulk transfers Material transfers Dedicated facility	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 6: Use a laboratory reagent**

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Laboratory activities	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Manufacture of substance - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC01

**Section 4: Guidance to check compliance with the exposure scenario**

<b>Environment</b>	Not available.
<b>Health</b>	Not available.

**Section 5. Remarks: Additional good practice advice beyond the REACH CSA**

<b>Environment</b>	Not applicable.
<b>Health</b>	Not applicable.
<b>Additional Good Practices</b>	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** *Manufacture of substance - Industrial*  
**Process Category:** *PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15*  
**Substance supplied to that use in form of:** *As such*  
**Sector of end use:** *SU03*  
**Subsequent service life relevant for that use:** *No.*  
**Environmental Release Category:** *ERC01*

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

Section 1: Title

**Short title of the exposure scenario/List of use descriptors** **Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d  
**Specific Environmental Release Category:** FEICA 7

**Processes and activities covered by the exposure scenario** Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

Section 2: Operational conditions and risk management measures

Section 2.1 Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

**Amounts used:** 10700 Tonnes/year  
**Fraction of EU tonnage used in region** 1  
**Regional use tonnage** Not available.  
**Fraction of Regional tonnage used locally** Not available.  
**Annual site tonnage** Not available.  
**Average Local Daily Tonnage (kg/day):** Not available.  
**Maximum daily site tonnage** 800  
**Frequency and duration of use:** Continuous release  
**Emission Days (days/year)** 220

**Environment factors not influenced by risk management:**  
**Local freshwater dilution factor** 10 Default  
**Local marine water dilution factor** 100 Default

**Other given operational conditions affecting environmental exposure:**  
**Release fraction to air from process (initial release prior to RMM)** 1.70E-02  
**Release fraction to soil from process (initial release prior to RMM)** 0.00E+00  
**Release fraction to wastewater from process (initial release prior to RMM)** 0.00E+00  
**Release fraction to air from wide dispersive use (regional only)** Not available.  
**Release fraction to soil from wide dispersive use (regional only)** Not available.

Diethylenetriamine, DETA

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d



Release fraction to wastewater from wide dispersive use	Not available.
<b>Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:</b>	
Treat air emission to provide a typical removal efficiency of	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of	Not available.
<b>Conditions and measures related to municipal sewage treatment plant:</b>	
Estimated substance removal from wastewater via on-site sewage treatment	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs	92.6%
Maximum allowable site tonnage (M <sub>safe</sub> ) based on release following total wastewater treatment removal	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

<b>Section 2.1 Control of environmental exposure</b>	
<b>Contributing scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers</b>	
Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region	1
Regional use tonnage	Not available.
Fraction of Regional tonnage used locally	Not available.
Annual site tonnage	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage	800
Frequency and duration of use:	Continuous release
Emission Days (days/year)	220
<b>Environment factors not influenced by risk management:</b>	
Local freshwater dilution factor	10 Default
Local marine water dilution factor	100 Default
<b>Other given operational conditions affecting environmental exposure:</b>	
Release fraction to air from process (initial release prior to RMM)	1.70E-02
Release fraction to soil from process (initial release prior to RMM)	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM)	0.00E+00
Release fraction to air from wide dispersive use (regional only)	Not available.
Release fraction to soil from wide dispersive use (regional only)	Not available.
Release fraction to wastewater from wide dispersive use	Not available.
<b>Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:</b>	

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC06c, ERC06d



Treat air emission to provide a typical removal efficiency of Not available.  
 Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of Not applicable.  
 If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of Not available.

**Conditions and measures related to municipal sewage treatment plant:**

Estimated substance removal from wastewater via on-site sewage treatment 92.6%

Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs 92.6%

Maximum allowable site tonnage (M<sub>safe</sub>) based on release following total wastewater treatment removal 214560 kg/day

Conditions and measures related to external recovery of waste: Dispose of waste product or used containers according to local regulations.

Local release to soil, kg/day: 0

Local release to air, kg/day: 14

Local release to sewage, kg/day: 0

Fraction of main source to local environment: 0.016

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

Product characteristics: Volatility: low  
 Concentration of substance in product: Covers percentage substance in the product up to 5%.  
 Physical state: Liquid.  
 Amounts used: Not applicable.  
 Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently)  
 Human factors not influenced by risk management: None identified.  
 Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented  
 Assumes activities are at ambient temperature (unless stated differently).  
 Contributing scenarios: Operational conditions and risk management measures

General exposures (closed systems): No other specific measures identified.

Storage closed systems: No other specific measures identified.

Respiratory protection: None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**

Product characteristics: Volatility: low  
 Concentration of substance in product: Covers percentage substance in the product up to 5%.  
 Physical state: Liquid.  
 Amounts used: Not applicable.  
 Frequency and duration of use: Covers daily exposures up to 8 hours (unless stated differently)  
 Human factors not influenced by risk management: None identified.  
 Other given operational conditions affecting workers exposure: Assumes a good basic standard of occupational hygiene is implemented  
 Assumes activities are at ambient temperature (unless stated differently).  
 Contributing scenarios: Operational conditions and risk management measures

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

General exposures (closed systems) With sample collection: No other specific measures identified.

Film formation - air drying closed systems: No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

Article formation in mould Batch process closed systems Machine Manual: No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 4 hours.

Article formation in mould Foaming open systems Machine Manual: No other specific measures identified.

Film formation - air drying open systems: No other specific measures identified.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

#### Product characteristics:

Concentration of substance in product:

Physical state:

#### Amounts used:

#### Frequency and duration of use:

#### Human factors not influenced by risk management:

#### Other given operational conditions affecting workers exposure:

#### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

#### Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 5: Spraying in industrial settings and applications

#### Product characteristics:

Concentration of substance in product:

Physical state:

#### Amounts used:

#### Frequency and duration of use:

#### Human factors not influenced by risk management:

#### Other given operational conditions affecting workers exposure:

#### Contributing scenarios: Operational conditions and risk management measures

Spraying (automatic/robotic) Manual: Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.

#### Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

#### Product characteristics:

Concentration of substance in product:

Physical state:

#### Amounts used:

#### Frequency and duration of use:

#### Human factors not influenced by risk management:

#### Other given operational conditions affecting workers exposure:

#### Contributing scenarios: Operational conditions and risk management measures

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

47/110

Material transfers Non-dedicated facility: Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

**Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers: No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

**Contributing scenario controlling worker exposure for 8: Roller application or brushing of adhesive and other coating**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production -  
Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05,  
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Dipping, immersion and pouring: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 10: Use a laboratory reagent

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: No other specific measures identified.

Respiratory protection:

None.

## Section 3: Exposure estimation

### Section 3.1 Environment - Exposure estimation

#### Contributing scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	Value	Justification	

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.315	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0	Not applicable.

### Section 3.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

	<b>Release from point source (local exposure estimation) kg/day</b>	<b>Total release for regional exposure estimation kg/day</b>	<b>Justification</b>
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

<b>Marine water mg/l</b>	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
<b>Intermittent release. mg/l</b>	Not applicable.	Not applicable.	Not applicable.
<b>Fresh water sediment mg/kg dwt</b>	Not applicable.	3.19	During emission
<b>Marine water sediment mg/kg dwt</b>	Not applicable.	0.315	During emission
<b>Agricultural soil averaged mg/kg dwt</b>	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
<b>Grassland averaged mg/kg dwt</b>	Not applicable.	0.107, 180 days	Not applicable.
<b>Groundwater mg/l</b>	Not applicable.	Not applicable.	Not applicable.
<b>During emission mg/m<sup>3</sup></b>	Not applicable.	Not applicable.	Not applicable.
<b>Annual average mg/m<sup>3</sup></b>	Not applicable.	0.0023	Not applicable.
<b>Annual deposition mg/m<sup>2</sup>/d</b>	Not applicable.	Not applicable.	Not applicable.
<b>Micro-organism mg/l</b>	Not applicable.	0	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	General exposures closed systems; Storage closed systems	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures closed systems; Storage closed systems	0.01	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	General exposures (closed systems) With sample collection; Film formation - air drying closed systems	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures (closed systems) With sample collection; Film formation - air drying closed systems	0.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d



Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) With sample collection; Film formation - air drying closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures (closed systems) With sample collection; Film formation - air drying closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures (closed systems) With sample collection; Film formation - air drying closed systems	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process closed systems Machine Manual	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process closed systems Machine Manual	2.58	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process closed systems Machine Manual	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Preparation of material for application Mixing operations (closed systems); Article formation in mould Batch process closed systems Machine Manual	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d



**Section 3.2 Workers - Exposure estimation**

**Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming open systems Machine Manual ; Film formation - air drying open systems	6.86; Not applicable; 6.86; 6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming open systems Machine Manual ; Film formation - air drying open systems	2.58; 0.60; 4.30; 4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming open systems Machine Manual ; Film formation - air drying open systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming open systems Machine Manual ; Film formation - air drying open systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Article formation in mould Foaming open systems Machine Manual ; Film formation - air drying open systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation**

**Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	2.58; 0.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 5: Spraying in industrial settings and applications

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Spraying (automatic/robotic) Manual; Aerosols	2.14; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Spraying (automatic/robotic) Manual; Aerosols	4.30; 0.20	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC06c, ERC06d

<b>Short term exposure, Systemic, Inhalable</b>	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Material transfers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 8: Roller application or brushing of adhesive and other coating

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Roller, spreader, flow application	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Roller, spreader, flow application	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Roller, spreader, flow application	Not applicable	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC06c, ERC06d

<b>Short term exposure, Systemic, Inhalable</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Dipping, immersion and pouring	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Dipping, immersion and pouring	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Dipping, immersion and pouring	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Dipping, immersion and pouring	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Dipping, immersion and pouring	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 10: Use a laboratory reagent

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Laboratory activities	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

**Section 4: Guidance to check compliance with the exposure scenario**

<b>Environment</b>	Not available.
<b>Health</b>	Not available.

**Section 5. Remarks: Additional good practice advice beyond the REACH CSA**

<b>Environment</b>	Not applicable.
<b>Health</b>	Not applicable.
<b>Additional Good Practices</b>	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production -  
Industrial

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05,  
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC06c, ERC06d

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

Section 1: Title

**Short title of the exposure scenario/List of use descriptors** **Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f  
**Specific Environmental Release Category:** FEICA 10

**Processes and activities covered by the exposure scenario** Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.

Section 2: Operational conditions and risk management measures

Section 2.1 Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

**Amounts used:** 10700 Tonnes/year  
**Fraction of EU tonnage used in region** 0.1  
**Regional use tonnage** Not available.  
**Fraction of Regional tonnage used locally** Not available.  
**Annual site tonnage** Not available.  
**Average Local Daily Tonnage (kg/day):** Not available.  
**Maximum daily site tonnage** 5.8  
**Frequency and duration of use:** Continuous release  
**Emission Days (days/year)** 365

**Environment factors not influenced by risk management:**  
**Local freshwater dilution factor** 10 Default  
**Local marine water dilution factor** 100 Default

**Other given operational conditions affecting environmental exposure:**  
**Release fraction to air from process (initial release prior to RMM)** 0  
**Release fraction to soil from process (initial release prior to RMM)** 0  
**Release fraction to wastewater from process (initial release prior to RMM)** 1.50E-02  
**Release fraction to air from wide dispersive use (regional only)** Not available.  
**Release fraction to soil from wide dispersive use (regional only)** Not available.

Diethylenetriamine, DETA

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

Release fraction to wastewater from wide dispersive use	Not available.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat air emission to provide a typical removal efficiency of	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of	Not available.
Conditions and measures related to municipal sewage treatment plant:	
Estimated substance removal from wastewater via on-site sewage treatment	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs	92.6%
Maximum allowable site tonnage (M <sub>Safe</sub> ) based on release following total wastewater treatment removal	1730 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

## Section 2.1 Control of environmental exposure

### Contributing scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region	0.1
Regional use tonnage	Not available.
Fraction of Regional tonnage used locally	Not available.
Annual site tonnage	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage	5.8
Frequency and duration of use:	Continuous release
Emission Days (days/year)	365
Environment factors not influenced by risk management:	
Local freshwater dilution factor	10 Default
Local marine water dilution factor	100 Default
Other given operational conditions affecting environmental exposure:	
Release fraction to air from process (initial release prior to RMM)	0
Release fraction to soil from process (initial release prior to RMM)	0
Release fraction to wastewater from process (initial release prior to RMM)	1.50E-02
Release fraction to air from wide dispersive use (regional only)	Not available.
Release fraction to soil from wide dispersive use (regional only)	Not available.
Release fraction to wastewater from wide dispersive use	Not available.
Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:	
Treat air emission to provide a typical removal efficiency of	Not available.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f



**Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of** Not applicable.

**If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of** Not available.

**Conditions and measures related to municipal sewage treatment plant:**

**Estimated substance removal from wastewater via on-site sewage treatment** 92.6%

**Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs** 92.6%

**Maximum allowable site tonnage ( $M_{\text{Safe}}$ ) based on release following total wastewater treatment removal** 1730 kg/day

**Conditions and measures related to external recovery of waste:** Dispose of waste product or used containers according to local regulations.

**Local release to soil, kg/day:** 0

**Local release to air, kg/day:** 0

**Local release to sewage, kg/day:** 8.80E-02

**Fraction of main source to local environment:** 0.002

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

General exposures (closed systems): No other specific measures identified.

Storage closed systems: No other specific measures identified.

**Respiratory protection:**

None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU02a, SU02b

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC08c, ERC08f

General exposures (closed systems) With sample collection: No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 5%.  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors.

Film formation - air drying: Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

#### Amounts used:

Not applicable.

#### Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

#### Human factors not influenced by risk management:

None identified.

#### Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented

Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear suitable gloves tested to EN374.

#### Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

#### Amounts used:

Not applicable.

#### Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

#### Human factors not influenced by risk management:

None identified.

#### Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented

Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers: Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

#### Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

#### Amounts used:

Not applicable.

#### Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

#### Human factors not influenced by risk management:

None identified.

#### Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented

Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU02a, SU02b

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC08c, ERC08f

62/110

Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers: Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 7: Roller application or brushing of adhesive and other coating

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 8: Spraying outside industrial settings and/or applications

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers percentage substance in the product up to 5%.

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Spraying Manual: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Wear a respirator conforming to EN140 with type A filter or better.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU02a, SU02b

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC08c, ERC08f

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Foaming Manual: Wear suitable gloves tested to EN374.

Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 10: Use a laboratory reagent

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

Laboratory activities: No other specific measures identified.

Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 5%.

Physical state:

Liquid.

Amounts used:

Not applicable.

Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

Human factors not influenced by risk management:

None identified.

Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

Contributing scenarios: Operational conditions and risk management measures

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU02a, SU02b

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC08c, ERC08f

Preparation of material for application Mixing operations (open systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

**Respiratory protection:**

None.

### Section 3: Exposure estimation

#### Section 3.1 Environment - Exposure estimation

**Contributing scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix**

	<b>Release from point source (local exposure estimation) kg/day</b>	<b>Total release for regional exposure estimation kg/day</b>	<b>Justification</b>
<b>Waste water</b>	Not applicable.	Not applicable.	Not applicable.
<b>Surface water</b>	Not applicable.	Not applicable.	Not applicable.
<b>air (direct + STP)</b>	Not applicable.	Not applicable.	Not applicable.
<b>Soil (direct releases only)</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
<b>Concentration in sewage (PECstp) mg/l</b>	Not applicable.	Not applicable.	
<b>Concentration in sewage sludge mg/kg dwt</b>	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Fresh water mg/l</b>	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0019; Surface water, Dissolved Annual average : 0.0019	Not applicable.
<b>Marine water mg/l</b>	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
<b>Intermittent release. mg/l</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
<b>Fresh water sediment mg/kg dwt</b>	Not applicable.	3.78	During emission
<b>Marine water sediment mg/kg dwt</b>	Not applicable.	0.375	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
<b>Agricultural soil averaged mg/kg dwt</b>	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
<b>Grassland averaged mg/kg dwt</b>	Not applicable.	0.011, 180 days	Not applicable.
<b>Groundwater mg/l</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
<b>During emission mg/m<sup>3</sup></b>	Not applicable.	Not applicable.	Not applicable.
<b>Annual average mg/m<sup>3</sup></b>	Not applicable.	2.06E-05	Not applicable.
<b>Annual deposition mg/m<sup>2</sup>/d</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Micro-organism mg/l</b>	Not applicable.	0.0032	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

### Section 3.1 Environment - Exposure estimation

#### Contributing scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PEC <sub>stp</sub> ) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0019; Surface water, Dissolved Annual average : 0.0019	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.78	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.375	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.011, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures closed systems; Storage closed systems	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures closed systems; Storage closed systems	0.01	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f



<b>Short term exposure, Systemic, Dermal</b>	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	General exposures (closed systems) With sample collection	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures (closed systems) With sample collection	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (closed systems)	2.58	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.2 Workers - Exposure estimation</b>			
<b>Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	6.86; Not applicable; 1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	6.02; 0.70; 8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.2 Workers - Exposure estimation</b>			
<b>Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	6.02; 0.70	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
	Not applicable.	Not applicable.	Not applicable.
<b>Diethylenetriamine, DETA</b>		<b>Identified use name:</b> Use as a PU curing agent for rigid foam production - Professional	
		<b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19	
		<b>Substance supplied to that use in form of:</b> As such	
		<b>Sector of end use:</b> SU02a, SU02b	
		<b>Subsequent service life relevant for that use:</b> No.	
		<b>Environmental Release Category:</b> ERC08c, ERC08f	

<b>Short term exposure, Systemic, Combined</b>			
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	1.37; 2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	12.90; 9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Material transfers Non-dedicated facility Drum/batch transfers Transfer from/pouring from containers; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Material transfers Dedicated facility Drum/batch transfers Transfer from/pouring from containers	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 7: Roller application or brushing of adhesive and other coating

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Roller, spreader, flow application	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Roller, spreader, flow application	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 8: Spraying outside industrial settings and/or applications

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Spraying Manual; Aerosols	5.36; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Spraying Manual; Aerosols	6.02; 0.28	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Spraying Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Spraying Manual; Aerosols	Not applicable	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Spraying Manual; Aerosols	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Foaming Manual	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures closed systems; Storage closed systems	8.60	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 10: Use a laboratory reagent

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Laboratory activities	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Laboratory activities	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU02a, SU02b

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC08c, ERC08f

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	7.07; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	3.01; 0.14	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 4: Guidance to check compliance with the exposure scenario**

<b>Environment</b>	Not available.
<b>Health</b>	Not available.

**Section 5. Remarks: Additional good practice advice beyond the REACH CSA**

<b>Environment</b>	Not applicable.
<b>Health</b>	Not applicable.
<b>Additional Good Practices</b>	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as a PU curing agent for rigid foam production - Professional

**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19

**Substance supplied to that use in form of:** As such

**Sector of end use:** SU02a, SU02b

**Subsequent service life relevant for that use:** No.

**Environmental Release Category:** ERC08c, ERC08f



Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

Section 1: Title

**Short title of the exposure scenario/List of use descriptors** **Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d  
**Specific Environmental Release Category:** FEICA 7

**Processes and activities covered by the exposure scenario** Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, spreader, dip, flow, fluidised bed on production lines and film formation) and equipment cleaning, maintenance and associated laboratory activities.

Section 2: Operational conditions and risk management measures

Section 2.1 Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics

**Amounts used:** 10700 Tonnes/year  
**Fraction of EU tonnage used in region** 1  
**Regional use tonnage** Not available.  
**Fraction of Regional tonnage used locally** Not available.  
**Annual site tonnage** Not available.  
**Average Local Daily Tonnage (kg/day):** Not available.  
**Maximum daily site tonnage** 800  
**Frequency and duration of use:** Continuous release  
**Emission Days (days/year)** 220

**Environment factors not influenced by risk management:**  
**Local freshwater dilution factor** 10 Default  
**Local marine water dilution factor** 100 Default

**Other given operational conditions affecting environmental exposure:**  
**Release fraction to air from process (initial release prior to RMM)** 1.70E-02  
**Release fraction to soil from process (initial release prior to RMM)** 0.00E+00  
**Release fraction to wastewater from process (initial release prior to RMM)** 0.00E+00  
**Release fraction to air from wide dispersive use (regional only)** Not available.  
**Release fraction to soil from wide dispersive use (regional only)** Not available.  
**Release fraction to wastewater from wide dispersive use** Not available.

Diethylenetriamine, DETA

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d



<b>Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:</b>	
Treat air emission to provide a typical removal efficiency of	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of	Not available.
<b>Conditions and measures related to municipal sewage treatment plant:</b>	
Estimated substance removal from wastewater via on-site sewage treatment	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs	92.6%
Maximum allowable site tonnage ( $M_{safe}$ ) based on release following total wastewater treatment removal	214560 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	14
Local release to sewage, kg/day:	0
Fraction of main source to local environment:	0.016

<b>Section 2.1 Control of environmental exposure</b>	
<b>Contributing scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers</b>	
Amounts used:	10700 Tonnes/year
Fraction of EU tonnage used in region	1
Regional use tonnage	Not available.
Fraction of Regional tonnage used locally	Not available.
Annual site tonnage	Not available.
Average Local Daily Tonnage (kg/day):	Not available.
Maximum daily site tonnage	800
Frequency and duration of use:	Continuous release
Emission Days (days/year)	220
<b>Environment factors not influenced by risk management:</b>	
Local freshwater dilution factor	10 Default
Local marine water dilution factor	100 Default
<b>Other given operational conditions affecting environmental exposure:</b>	
Release fraction to air from process (initial release prior to RMM)	1.70E-02
Release fraction to soil from process (initial release prior to RMM)	0.00E+00
Release fraction to wastewater from process (initial release prior to RMM)	0.00E+00
Release fraction to air from wide dispersive use (regional only)	Not available.
Release fraction to soil from wide dispersive use (regional only)	Not available.
Release fraction to wastewater from wide dispersive use	Not available.
<b>Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:</b>	
Treat air emission to provide a typical removal efficiency of	Not available.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

**Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of** Not applicable.

**If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of** Not available.

**Conditions and measures related to municipal sewage treatment plant:**

**Estimated substance removal from wastewater via on-site sewage treatment** 92.6%

**Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs** 92.6%

**Maximum allowable site tonnage ( $M_{safe}$ ) based on release following total wastewater treatment removal** 214560 kg/day

**Conditions and measures related to external recovery of waste:** Dispose of waste product or used containers according to local regulations.

**Local release to soil, kg/day:** 0

**Local release to air, kg/day:** 14

**Local release to sewage, kg/day:** 0

**Fraction of main source to local environment:** 0.016

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

**Product characteristics:** Volatility: low

**Concentration of substance in product:** Covers concentrations up to 50%

**Physical state:** Liquid.

**Amounts used:** Not applicable.

**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:** None identified.

**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

General exposures (closed systems): No other specific measures identified.

Bulk product storage closed systems: No other specific measures identified.

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**

**Product characteristics:** Volatility: low

**Concentration of substance in product:** Covers concentrations up to 50%

**Physical state:** Liquid.

**Amounts used:** Not applicable.

**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:** None identified.

**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

General exposures (closed systems) With sample collection: No other specific measures identified.

Injection moulding of articles closed systems: No other specific measures identified.

Film formation - air drying closed systems: No other specific measures identified.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
Preparation of material for application Mixing operations (closed systems): No other specific measures identified.

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
Preparation of material for application Mixing operations (open systems): Provide extract ventilation to points where emissions occur.

Film formation - air drying open systems: Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

Preparation of material for application Mixing operations (open systems): Provide extract ventilation to points where emissions occur.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 5: Spraying in industrial settings and applications

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Spraying (automatic/robotic) Manual: Apply within a vented cab supplied with filtered air under positive pressure and with a protection factor of >20.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

77/110

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility: Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 8: Roller application or brushing of adhesive and other coating**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05,  
PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

Dipping, immersion and pouring: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 10: Use a laboratory reagent**

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
 Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

**Respiratory protection:** None.

**Section 3: Exposure estimation**

**Section 3.1 Environment - Exposure estimation**

**Contributing scenario controlling environmental exposure for 0: Industrial use of monomers for manufacture of thermoplastics**

	<b>Release from point source (local exposure estimation) kg/day</b>	<b>Total release for regional exposure estimation kg/day</b>	<b>Justification</b>
<b>Waste water</b>	Not applicable.	Not applicable.	Not applicable.
<b>Surface water</b>	Not applicable.	Not applicable.	Not applicable.
<b>air (direct + STP)</b>	Not applicable.	Not applicable.	Not applicable.
<b>Soil (direct releases only)</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
<b>Concentration in sewage (PECstp) mg/l</b>	Not applicable.	Not applicable.	
<b>Concentration in sewage sludge mg/kg dwt</b>	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Fresh water mg/l</b>	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.31	During emission
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
Micro-organism mg/l	Not applicable.	0	Not applicable.

### Section 3.1 Environment - Exposure estimation

#### Contributing scenario controlling environmental exposure for 1: Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers

	Release from point source (local exposure estimation) kg/day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PEC <sub>stp</sub> ) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
Fresh water mg/l	Not applicable.	PEC aquatic (local+regional)	Justification
		Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.0017; Surface water, Dissolved Annual average : 0.0017	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.19	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.31	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.798, 30 days; 0.264, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.107, 180 days	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d



Groundwater mg/l	Not applicable. <b>Local concentration</b>	Not applicable. <b>PEC air (local+regional)</b>	Not applicable. <b>Justification</b>
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	0.0023	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable. <b>Local concentration</b>	Not applicable. <b>PEC aquatic (local+regional)</b>	Not applicable. <b>Justification</b>
Micro-organism mg/l	Not applicable.	0	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures closed systems; Bulk product storage closed systems	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures closed systems; Bulk product storage closed systems	0.02	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures (closed systems) With sample collection; Injection moulding of articles closed systems; Film formation - air drying closed systems	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures (closed systems) With sample collection; Injection moulding of articles closed systems; Film formation - air drying closed systems	2.15	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures (closed systems) With sample collection; Injection moulding of articles closed systems; Film formation - air drying closed systems	Not applicable	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

<b>Short term exposure, Systemic, Inhalable</b>	General exposures (closed systems) With sample collection; Injection moulding of articles closed systems; Film formation - air drying closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures (closed systems) With sample collection; Injection moulding of articles closed systems; Film formation - air drying closed systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems)	6.45	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems)	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying open systems	0.69; Not applicable; 1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures closed systems; Bulk product storage closed systems	1.07; 0.25; 10.75	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures closed systems; Bulk product storage closed systems	Not applicable	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

<b>Short term exposure, Systemic, Inhalable</b>	General exposures closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	0.07; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	1.07; 0.25	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 5: Spraying in industrial settings and applications

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Spraying (automatic/robotic) Manual; Aerosols	2.14; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Spraying (automatic/robotic) Manual; Aerosols	10.75; 0.50	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Spraying (automatic/robotic) Manual; Aerosols	Not applicable	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
---------------------------------------	-----------------	-----------------	-----------------

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 7: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures closed systems; Bulk product storage closed systems	10.75	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures closed systems; Bulk product storage closed systems	Not applicable	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 8: Roller application or brushing of adhesive and other coating

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Roller, spreader, flow application	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Roller, spreader, flow application	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Dipping, immersion and pouring	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Dipping, immersion and pouring	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Dipping, immersion and pouring	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Dipping, immersion and pouring	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Dipping, immersion and pouring	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 10: Use a laboratory reagent**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Laboratory activities	7.52	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 4: Guidance to check compliance with the exposure scenario**

<b>Environment</b>	Not available.
<b>Health</b>	Not available.

**Section 5. Remarks: Additional good practice advice beyond the REACH CSA**

<b>Environment</b>	Not applicable.
<b>Health</b>	Not applicable.
<b>Additional Good Practices</b>	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC07, PROC08a, PROC08b, PROC10, PROC13, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06c, ERC06d



Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

Section 1: Title

**Short title of the exposure scenario/List of use descriptors** **Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f  
**Specific Environmental Release Category:** FEICA 10

**Processes and activities covered by the exposure scenario** Covers the use in coatings (paints, inks, adhesives, etc) including exposures during use (including materials receipt, storage, preparation and transfer from bulk and semi-bulk, application by spray, roller, brush, spreader by hand or similar methods, and film formation), and equipment cleaning, maintenance and associated laboratory activities.

Section 2: Operational conditions and risk management measures

Section 2.1 Control of environmental exposure

Contributing scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

**Amounts used:** 10700 Tonnes/year  
**Fraction of EU tonnage used in region** 0.1  
**Regional use tonnage** Not available.  
**Fraction of Regional tonnage used locally** Not available.  
**Annual site tonnage** Not available.  
**Average Local Daily Tonnage (kg/day):** Not available.  
**Maximum daily site tonnage** 5.8  
**Frequency and duration of use:** Continuous release  
**Emission Days (days/year)** 365

**Environment factors not influenced by risk management:**  
**Local freshwater dilution factor** 10 Default  
**Local marine water dilution factor** 100 Default

**Other given operational conditions affecting environmental exposure:**  
**Release fraction to air from process (initial release prior to RMM)** 0.00E+00  
**Release fraction to soil from process (initial release prior to RMM)** 0.00E+00  
**Release fraction to wastewater from process (initial release prior to RMM)** 1.50E-02  
**Release fraction to air from wide dispersive use (regional only)** Not available.  
**Release fraction to soil from wide dispersive use (regional only)** Not available.  
**Release fraction to wastewater from wide dispersive use** Not available.

Diethylenetriamine, DETA

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f



**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:**

Treat air emission to provide a typical removal efficiency of	Not available.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of	Not applicable.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of	Not available.

**Conditions and measures related to municipal sewage treatment plant:**

Estimated substance removal from wastewater via on-site sewage treatment 92.6%

Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs 92.6%

Maximum allowable site tonnage ( $M_{safe}$ ) based on release following total wastewater treatment removal 1730 kg/day

Conditions and measures related to external recovery of waste: Dispose of waste product or used containers according to local regulations.

Local release to soil, kg/day: 0

Local release to air, kg/day: 0

Local release to sewage, kg/day: 8.80E-02

Fraction of main source to local environment: 0.002

**Section 2.1 Control of environmental exposure**

**Contributing scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix**

Amounts used: 10700 Tonnes/year

Fraction of EU tonnage used in region 0.1

Regional use tonnage Not available.

Fraction of Regional tonnage used locally Not available.

Annual site tonnage Not available.

Average Local Daily Tonnage (kg/day): Not available.

Maximum daily site tonnage 5.8

Frequency and duration of use: Continuous release

Emission Days (days/year) 365

**Environment factors not influenced by risk management:**

Local freshwater dilution factor 10 Default

Local marine water dilution factor 100 Default

**Other given operational conditions affecting environmental exposure:**

Release fraction to air from process (initial release prior to RMM) 0.00E+00

Release fraction to soil from process (initial release prior to RMM) 0.00E+00

Release fraction to wastewater from process (initial release prior to RMM) 1.50E-02

Release fraction to air from wide dispersive use (regional only) Not available.

Release fraction to soil from wide dispersive use (regional only) Not available.

Release fraction to wastewater from wide dispersive use Not available.

**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:**

Treat air emission to provide a typical removal efficiency of Not available.

Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of	Not available.
<b>Conditions and measures related to municipal sewage treatment plant:</b>	
Estimated substance removal from wastewater via on-site sewage treatment	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs	92.6%
Maximum allowable site tonnage (M <sub>Safe</sub> ) based on release following total wastewater treatment removal	1730 kg/day
<b>Conditions and measures related to external recovery of waste:</b>	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	0
Local release to air, kg/day:	0
Local release to sewage, kg/day:	8.80E-02
Fraction of main source to local environment:	0.002

**Section 2.2 Control of worker exposure**  
**Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**  
**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
General exposures (closed systems): No other specific measures identified.  
Storage closed systems: No other specific measures identified.  
  
**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**  
**Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**  
**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
General exposures (closed systems) With sample collection: No other specific measures identified.  
  
**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

**89/110**

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

#### Amounts used:

Not applicable.

#### Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

#### Human factors not influenced by risk management:

None identified.

#### Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (closed systems): Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors.

#### Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

#### Amounts used:

Not applicable.

#### Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

#### Human factors not influenced by risk management:

None identified.

#### Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 1 hour.

Film formation - air drying: Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

#### Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers concentrations up to 50%

Physical state:

Liquid.

#### Amounts used:

Not applicable.

#### Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

#### Human factors not influenced by risk management:

None identified.

#### Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

90/110

Preparation of material for application Mixing operations (open systems): Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

<b>Product characteristics:</b>	Volatility: low
<b>Concentration of substance in product:</b>	Covers concentrations up to 50%
<b>Physical state:</b>	Liquid.
<b>Amounts used:</b>	Not applicable.
<b>Frequency and duration of use:</b>	Covers daily exposures up to 8 hours (unless stated differently)
<b>Human factors not influenced by risk management:</b>	None identified.
<b>Other given operational conditions affecting workers exposure:</b>	Assumes a good basic standard of occupational hygiene is implemented Assumes activities are at ambient temperature (unless stated differently).
<b>Contributing scenarios: Operational conditions and risk management measures</b>	

Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with type A filter or better.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with type A filter or better.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

<b>Product characteristics:</b>	Volatility: low
<b>Concentration of substance in product:</b>	Covers concentrations up to 50%
<b>Physical state:</b>	Liquid.
<b>Amounts used:</b>	Not applicable.
<b>Frequency and duration of use:</b>	Covers daily exposures up to 8 hours (unless stated differently)
<b>Human factors not influenced by risk management:</b>	None identified.
<b>Other given operational conditions affecting workers exposure:</b>	Assumes a good basic standard of occupational hygiene is implemented Assumes activities are at ambient temperature (unless stated differently).
<b>Contributing scenarios: Operational conditions and risk management measures</b>	

Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility: Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

91/110

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 7: Roller application or brushing of adhesive and other coating

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Roller, spreader, flow application: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear chemical-resistant gloves (tested to EN374) in combination with 'basic' employee training.

**Respiratory protection:**

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 8: Spraying outside industrial settings and/or applications

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

Spraying Manual: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). or Ensure operation is undertaken outdoors. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training. Wear a respirator conforming to EN140 with type A filter or better.

**Respiratory protection:**

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring

**Product characteristics:**

Volatility: low

**Concentration of substance in product:**

Covers concentrations up to 50%

**Physical state:**

Liquid.

**Amounts used:**

Not applicable.

**Frequency and duration of use:**

Covers daily exposures up to 8 hours (unless stated differently)

**Human factors not influenced by risk management:**

None identified.

**Other given operational conditions affecting workers exposure:**

Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).

**Contributing scenarios: Operational conditions and risk management measures**

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

92/110

Dipping, immersion and pouring: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 10: Use a laboratory reagent

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
Laboratory activities: No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers concentrations up to 50%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**  
Preparation of material for application Mixing operations (open systems): Wear a respirator conforming to EN140 with type A filter or better. Wear chemical-resistant gloves (tested to EN374) in combination with specific activity training.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

93/110

### Section 3: Exposure estimation

#### Section 3.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 0: Wide dispersive indoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.002; Surface water, Dissolved Annual average : 0.002	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.678	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.374	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.0106, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

#### Section 3.1 Environment - Exposure estimation

Contributing scenario controlling environmental exposure for 1: Wide dispersive outdoor use resulting in inclusion into or onto a matrix

	Release from point source (local exposure estimation) kg/ day	Total release for regional exposure estimation kg/day	Justification
Waste water	Not applicable.	Not applicable.	Not applicable.
Surface water	Not applicable.	Not applicable.	Not applicable.
air (direct + STP)	Not applicable.	Not applicable.	Not applicable.
Soil (direct releases only)	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05,  
 PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f



	Value	Justification	
Concentration in sewage (PECstp) mg/l	Not applicable.	Not applicable.	
Concentration in sewage sludge mg/kg dwt	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Fresh water mg/l	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.002; Surface water, Dissolved Annual average : 0.002	Not applicable.
Marine water mg/l	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.0002; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.0002	Not applicable.
Intermittent release. mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
Fresh water sediment mg/kg dwt	Not applicable.	3.678	During emission
Marine water sediment mg/kg dwt	Not applicable.	0.374	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
Agricultural soil averaged mg/kg dwt	Not applicable.	0.071, 30 days; 0.024, 180 days	Not applicable.
Grassland averaged mg/kg dwt	Not applicable.	0.0106, 180 days	Not applicable.
Groundwater mg/l	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
During emission mg/m <sup>3</sup>	Not applicable.	Not applicable.	Not applicable.
Annual average mg/m <sup>3</sup>	Not applicable.	2.06E-05	Not applicable.
Annual deposition mg/m <sup>2</sup> /d	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
Micro-organism mg/l	Not applicable.	0.0032	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
Long term exposure, Systemic, Dermal	General exposures closed systems; Storage closed systems	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Inhalable	General exposures closed systems; Storage closed systems	0.02	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
Long term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Dermal	Not applicable.	Not applicable.	Not applicable.
Long term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Systemic, Dermal	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Inhalable	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
Short term exposure, Systemic, Combined	Not applicable.	Not applicable.	Not applicable.
Short term exposure, Local, Dermal	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
Short term exposure, Local, Inhalable	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	General exposures (closed systems) With sample collection	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures (closed systems) With sample collection	10.75	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures (closed systems) With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (closed systems)	4.51	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (closed systems)	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying open systems	6.86; Not applicable; 1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying open systems	4.30; 0.50; 12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying open systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying open systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols; Film formation - air drying open systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 4: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	2.74; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	4.30; 0.50	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.2 Workers - Exposure estimation</b>			
<b>Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	5.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Non-dedicated facility; Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Section 3.2 Workers - Exposure estimation</b>			
<b>Contributing scenario controlling worker exposure for 6: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities</b>			
<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Material transfers Drum/batch transfers Transfer from/pouring from containers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures closed systems; Storage closed systems	12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
<b>Diethylenetriamine, DETA</b>			
<p><b>Identified use name:</b> Use as an epoxy curing agent - Professional  <b>Process Category:</b> PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  <b>Substance supplied to that use in form of:</b> As such  <b>Sector of end use:</b> SU02a, SU02b  <b>Subsequent service life relevant for that use:</b> No.  <b>Environmental Release Category:</b> ERC08c, ERC08f</p>			

<b>Short term exposure, Systemic, Inhalable</b>	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures closed systems; Storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 7: Roller application or brushing of adhesive and other coating

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Roller, spreader, flow application	5.49	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Roller, spreader, flow application	3.76	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Roller, spreader, flow application	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

### Section 3.2 Workers - Exposure estimation

#### Contributing scenario controlling worker exposure for 8: Spraying outside industrial settings and/or applications

Route of exposure	Contributing scenarios	Dose/Concentration	Justification
<b>Long term exposure, Systemic, Dermal</b>	Spraying Manual; Aerosols	0.11; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Spraying Manual; Aerosols	15.05; 0.70	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Spraying Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Spraying Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Spraying Manual; Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 9: Treatment of articles by dipping and pouring**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Dipping, immersion and pouring	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Dipping, immersion and pouring	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Dipping, immersion and pouring	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Dipping, immersion and pouring	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Dipping, immersion and pouring	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 10: Use a laboratory reagent**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Laboratory activities	10.75	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 11: Hand-mixing with intimate contact and only PPE available**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	7.07; Not applicable	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	5.37; 0.25	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f



<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Preparation of material for application Mixing operations (open systems); Aerosols	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

#### Section 4: Guidance to check compliance with the exposure scenario

<b>Environment</b>	Not available.
<b>Health</b>	Not available.

#### Section 5. Remarks: Additional good practice advice beyond the REACH CSA

<b>Environment</b>	Not applicable.
<b>Health</b>	Not applicable.
<b>Additional Good Practices</b>	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an epoxy curing agent - Professional  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC10, PROC11, PROC13, PROC15, PROC19  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU02a, SU02b  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC08c, ERC08f



Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

**Product definition** Mono-constituent substance  
**Product name** Diethylenetriamine, DETA

Section 1: Title

**Short title of the exposure scenario/List of use descriptors** **Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a  
**Specific Environmental Release Category:** ESVOC 2

**Processes and activities covered by the exposure scenario** Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

Section 2: Operational conditions and risk management measures

Section 2.1 Control of environmental exposure

**Contributing scenario controlling environmental exposure for 0: Industrial use resulting in manufacture of another substance (use of intermediates)**

<b>Amounts used:</b>	43000 Tonnes/year
<b>Fraction of EU tonnage used in region</b>	1
<b>Regional use tonnage</b>	Not available.
<b>Fraction of Regional tonnage used locally</b>	Not available.
<b>Annual site tonnage</b>	Not available.
<b>Average Local Daily Tonnage (kg/day):</b>	Not available.
<b>Maximum daily site tonnage</b>	14333
<b>Frequency and duration of use:</b>	Continuous release
<b>Emission Days (days/year)</b>	300

**Environment factors not influenced by risk management:**

<b>Local freshwater dilution factor</b>	10 Default
<b>Local marine water dilution factor</b>	100 Default

**Other given operational conditions affecting environmental exposure:**

<b>Release fraction to air from process (initial release prior to RMM)</b>	2.00E-05
<b>Release fraction to soil from process (initial release prior to RMM)</b>	1.00E-003
<b>Release fraction to wastewater from process (initial release prior to RMM)</b>	1.00E-02
<b>Release fraction to air from wide dispersive use (regional only)</b>	Not available.
<b>Release fraction to soil from wide dispersive use (regional only)</b>	Not available.
<b>Release fraction to wastewater from wide dispersive use</b>	Not available.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

**Technical on-site conditions and measures to reduce or limit discharges, air emissions and releases to soil:**

Treat air emission to provide a typical removal efficiency of	Not applicable.
Treat on-site wastewater (prior to receiving water discharge) to provide the required removal efficiency of	Not available.
If discharging to domestic sewage treatment plant, provide the required onsite wastewater removal efficiency of	Not available.

**Conditions and measures related to municipal sewage treatment plant:**

Estimated substance removal from wastewater via on-site sewage treatment	92.6%
Total efficiency of removal from wastewater after on-site and off-site (domestic treatment plant) RMMs	92.6%
Maximum allowable site tonnage ( $M_{safe}$ ) based on release following total wastewater treatment removal	15640 kg/day
Conditions and measures related to external recovery of waste:	Dispose of waste product or used containers according to local regulations.
Local release to soil, kg/day:	14.3
Local release to air, kg/day:	2.86E-01
Local release to sewage, kg/day:	143.3
Fraction of main source to local environment:	0.1

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently)
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	
General exposures Continuous process closed systems:	No other specific measures identified.

Bulk product storage closed systems: No other specific measures identified.

**Respiratory protection:** None.

**Section 2.2 Control of worker exposure**

**Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**

Product characteristics:	Volatility: low
Concentration of substance in product:	Covers percentage substance in the product up to 100%
Physical state:	Liquid.
Amounts used:	Not applicable.
Frequency and duration of use:	Covers daily exposures up to 8 hours (unless stated differently)
Human factors not influenced by risk management:	None identified.
Other given operational conditions affecting workers exposure:	Assumes a good basic standard of occupational hygiene is implemented Assumes activities are at ambient temperature (unless stated differently).
Contributing scenarios: Operational conditions and risk management measures	

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

General exposures Continuous process With sample collection closed systems: No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**

General exposures Use in contained batch processes With sample collection: No other specific measures identified.

**Respiratory protection:** None.

### Section 2.2 Control of worker exposure

#### Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises

**Product characteristics:** Volatility: low  
**Concentration of substance in product:** Covers percentage substance in the product up to 100%  
**Physical state:** Liquid.  
**Amounts used:** Not applicable.  
**Frequency and duration of use:** Covers daily exposures up to 8 hours (unless stated differently)  
**Human factors not influenced by risk management:** None identified.  
**Other given operational conditions affecting workers exposure:** Assumes a good basic standard of occupational hygiene is implemented  
Assumes activities are at ambient temperature (unless stated differently).  
**Contributing scenarios: Operational conditions and risk management measures**

General exposures Batch process With sample collection open systems: Provide extract ventilation to points where emissions occur.

**Respiratory protection:** None.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

#### Amounts used:

Not applicable.

#### Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

#### Human factors not influenced by risk management:

None identified.

#### Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented

Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Equipment cleaning and maintenance: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 1 hour. Wear suitable gloves tested to EN374.

Equipment cleaning and maintenance: Wear suitable gloves tested to EN374. Wear a respirator conforming to EN140 with type A filter or better.

#### Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

#### Amounts used:

Not applicable.

#### Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

#### Human factors not influenced by risk management:

None identified.

#### Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented

Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

Bulk transfers Material transfers Dedicated facility: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Ensure operation is undertaken outdoors. Avoid carrying out activities involving exposure for more than 4 hours. Wear suitable gloves tested to EN374.

#### Respiratory protection:

None.

## Section 2.2 Control of worker exposure

### Contributing scenario controlling worker exposure for 6: Use a laboratory reagent

#### Product characteristics:

Volatility: low

Concentration of substance in product:

Covers percentage substance in the product up to 100%

Physical state:

Liquid.

#### Amounts used:

Not applicable.

#### Frequency and duration of use:

Covers daily exposures up to 8 hours (unless stated differently)

#### Human factors not influenced by risk management:

None identified.

#### Other given operational conditions affecting workers exposure:

Assumes a good basic standard of occupational hygiene is implemented

Assumes activities are at ambient temperature (unless stated differently).

#### Contributing scenarios: Operational conditions and risk management measures

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a,  
PROC08b, PROC15

**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03

**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

105/110

Laboratory activities: Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour). Avoid carrying out activities involving exposure for more than 4 hours.

**Respiratory protection:**

None.

### Section 3: Exposure estimation

#### Section 3.1 Environment - Exposure estimation

**Contributing scenario controlling environmental exposure for 0: Industrial use resulting in manufacture of another substance (use of intermediates)**

	<b>Release from point source (local exposure estimation) kg/day</b>	<b>Total release for regional exposure estimation kg/day</b>	<b>Justification</b>
<b>Waste water</b>	Not applicable.	Not applicable.	Not applicable.
<b>Surface water</b>	Not applicable.	Not applicable.	Not applicable.
<b>air (direct + STP)</b>	Not applicable.	Not applicable.	Not applicable.
<b>Soil (direct releases only)</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Value</b>	<b>Justification</b>	
<b>Concentration in sewage (PEC<sub>stp</sub>) mg/l</b>	Not applicable.	Not applicable.	
<b>Concentration in sewage sludge mg/kg dwt</b>	Not applicable.	Not applicable.	
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Fresh water mg/l</b>	Not applicable.	Surface water, Dissolved During emission Resulting PEC local, water (mg/l): 0.513; Surface water, Dissolved Annual average : 0.442	Not applicable.
<b>Marine water mg/l</b>	Not applicable.	During emission Resulting PEC local, water (mg/l): 0.051; Annual average, Dissolved, Resulting PEC local, water (mg/l): 0.042	Not applicable.
<b>Intermittent release. mg/l</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC sediment (local+regional)</b>	<b>Justification</b>
<b>Fresh water sediment mg/kg dwt</b>	Not applicable.	982.6	During emission
<b>Marine water sediment mg/kg dwt</b>	Not applicable.	98.23	During emission
	<b>Local concentration</b>	<b>PEC soil (local+regional)</b>	<b>Justification</b>
<b>Agricultural soil averaged mg/kg dwt</b>	Not applicable.	114.1, 30 days; 37.5, 180 days	Not applicable.
<b>Grassland averaged mg/kg dwt</b>	Not applicable.	15.0, 180 days	Not applicable.
<b>Groundwater mg/l</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC air (local+regional)</b>	<b>Justification</b>
<b>During emission mg/m<sup>3</sup></b>	Not applicable.	Not applicable.	Not applicable.
<b>Annual average mg/m<sup>3</sup></b>	Not applicable.	8.6E-05	Not applicable.
<b>Annual deposition mg/m<sup>2</sup>/d</b>	Not applicable.	Not applicable.	Not applicable.
	<b>Local concentration</b>	<b>PEC aquatic (local+regional)</b>	<b>Justification</b>
<b>Micro-organism mg/l</b>	Not applicable.	5.262	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

106/110

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 0: Use in closed process, no likelihood of exposure**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	General exposures Continuous process closed systems; Bulk product storage closed systems	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures Continuous process closed systems; Bulk product storage closed systems	0.04	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures Continuous process closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures Continuous process closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures Continuous process closed systems; Bulk product storage closed systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 1: Use in closed, continuous process with occasional controlled exposure**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	General exposures Continuous process With sample collection closed systems	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures Continuous process With sample collection closed systems	4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures Continuous process With sample collection closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures Continuous process With sample collection closed systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures Continuous process With sample collection closed systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 2: Use in closed batch process (synthesis or formulation)**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	General exposures Use in contained batch processes With sample collection	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures Use in contained batch processes With sample collection	12.90	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures Use in contained batch processes With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures Use in contained batch processes With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures Use in contained batch processes With sample collection	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 3: Use in batch and other process (synthesis) where opportunity for exposure arises**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	General exposures Batch process With sample collection open systems	6.86	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	General exposures Batch process With sample collection open systems	2.15	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	General exposures Batch process With sample collection open systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	General exposures Batch process With sample collection open systems	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	General exposures Batch process With sample collection open systems	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a



**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 4: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Equipment cleaning and maintenance	2.74	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Equipment cleaning and maintenance	6.02; 4.30	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Equipment cleaning and maintenance	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 5: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Bulk transfers Material transfers Dedicated facility	1.37	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Bulk transfers Material transfers Dedicated facility	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Bulk transfers Material transfers Dedicated facility	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a

**Section 3.2 Workers - Exposure estimation****Contributing scenario controlling worker exposure for 6: Use a laboratory reagent**

<b>Route of exposure</b>	<b>Contributing scenarios</b>	<b>Dose/Concentration</b>	<b>Justification</b>
<b>Long term exposure, Systemic, Dermal</b>	Laboratory activities	0.34	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Inhalable</b>	Laboratory activities	9.03	The ECETOC TRA tool has been used to estimate workplace exposures unless otherwise indicated.
<b>Long term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Dermal</b>	Not applicable.	Not applicable.	Not applicable.
<b>Long term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Systemic, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Inhalable</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Systemic, Combined</b>	Not applicable.	Not applicable.	Not applicable.
<b>Short term exposure, Local, Dermal</b>	Laboratory activities	Not applicable	Not applicable.
<b>Short term exposure, Local, Inhalable</b>	Not applicable.	Not applicable.	Not applicable.

**Section 4: Guidance to check compliance with the exposure scenario**

<b>Environment</b>	Not available.
<b>Health</b>	Not available.

**Section 5. Remarks: Additional good practice advice beyond the REACH CSA**

<b>Environment</b>	Not applicable.
<b>Health</b>	Not applicable.
<b>Additional Good Practices</b>	Not applicable.

**Diethylenetriamine, DETA**

**Identified use name:** Use as an intermediate - Industrial  
**Process Category:** PROC01, PROC02, PROC03, PROC04, PROC08a, PROC08b, PROC15  
**Substance supplied to that use in form of:** As such  
**Sector of end use:** SU03  
**Subsequent service life relevant for that use:** No.  
**Environmental Release Category:** ERC06a